



**US Army Corps
of Engineers**
Waterways Experiment
Station

Compilation of Suspended-Load Point-Transport Theories

*by Thomas G. Drake, Evans-Hamilton, Inc.
Thomas E. White, WES*

WES

Approved For Public Release; Distribution is Unlimited

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.



PRINTED ON RECYCLED PAPER

Compilation of Suspended-Load Point-Transport Theories

by Thomas G. Drake

Evans-Hamilton, Inc.
7214 S. Kirkwood
Houston, TX 77072

Thomas E. White


U.S. Army Corps of Engineers
Waterways Experiment Station
3909 Halls Ferry Road
Vicksburg, MS 39180-6199

Final report

Approved for public release; distribution is unlimited



**US Army Corps
of Engineers**
Waterways Experiment
Station



FOR INFORMATION CONTACT:
PUBLIC AFFAIRS OFFICE
U. S. ARMY ENGINEER
WATERWAYS EXPERIMENT STATION
3808 HALLS FERRY ROAD
VICKSBURG, MISSISSIPPI 39180-6199
PHONE: (601)634-2502

Waterways Experiment Station Cataloging-in-Publication Data

Drake, Thomas G.

Compilation of suspended-load point-transport theories / by Thomas G. Drake, Thomas E. White ; prepared for U.S. Army Corps of Engineers. 40 p. : ill. ; 28 cm. — (Technical report ; CERC-95-18)

Includes bibliographic references.

1. Suspended sediments. 2. Sediment transport. 3. Marine sediments. I. White, Thomas E. II. United States. Army. Corps of Engineers. III. U.S. Army Engineer Waterways Experiment Station. IV. Coastal Engineering Research Center (U.S. Army Engineer Waterways Experiment Station) V. Title. VI. Series: Technical report (U.S. Army Engineer Waterways Experiment Station) ; CERC-95-18.

TA7 W34 no.CERC-95-18

Contents

Preface	iv
1—Introduction	1
Background	1
Organization	1
Selection Criteria	1
2—Theory	3
Energetics-Based Theories for Suspended-Sediment	
Transport	3
Bowen (1980)	6
Bailard (1981; 1982; 1987)	6
Roelvink and Stive (1989)	8
Humiston (1993)	8
Bed friction and suspended sediment efficiency	
factors	9
Diffusion-Based Theories for Suspended-Sediment	
Transport	10
Dally and Dean (1984)	12
Deigaard, Fredsoe, and Hedegaard (1986)	12
Semi-Empirical Models for Suspended Sediment	
Transport	13
Larson and Kraus (1989)	13
SBEACH parameters	16
Ackers and White (1973)	17
References	20
Bibliography	24
Appendix A: Notation	A1

SF298

Preface

This contract report summarizes a literature review of suspended-sediment transport theories under oscillatory flow conditions performed by Dr. Thomas G. Drake. The work was performed under Evans-Hamilton, Inc., Contract No. DACW39-92-D-0012 with the U.S. Army Engineer Waterways Experiment Station's (WES) Coastal Engineering Research Center (CERC).

This report supplies a list of suspended-sediment transport theories to be tested with field data collected by personnel in the Prototype Measurement and Analysis Branch, CERC. Dr. Thomas White was Principal Investigator and provided technical oversight for Work Unit 32685 "Field Tests of Sediment Transport Theories" in the Coastal Research Program at CERC. The work unit continues under the Inlets Research Program.

WES supervisors during this report's preparation were Branch Chief William L. Preslan, Division Chief Thomas W. Richardson, Program Manager Carolyn M. Holmes, Assistant Director of CERC Charles C. Calhoun, Jr., Director of CERC Dr. James R. Houston, Director of WES Dr. Robert W. Whalin, and Commander of WES COL Bruce K. Howard, EN.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

1 Introduction

Background

Numerous theories are available to predict the transport of cohesionless sediments by suspension in the surf zone. The purpose of this report is to survey the available literature for such theories; and, subject to certain criteria discussed below, to differentiate between unique theories and essentially redundant ones. For each of the unique theories, a common set of variables is used to formulate an explicit mathematical expression for the suspended sediment transport rate. Redundant theories are those which differ only by numerical coefficients from any of the unique theories, having otherwise the same functional form. Accompanying each unique formula is an outline of its derivation, and a list of the assumptions underlying the derivation. The selected formulae will form a basis for testing theoretical predictions with field measurements of suspended-sediment transport and requisite fluid and sediment quantities at a point within the surf zone or immediately adjacent to it.

Organization

The organization of the report is as follows: first, the criteria used to select theories from the literature are presented; second, a section on theory discusses general considerations, and presents each of the unique formulas, their derivation, and assumptions. A table of selected theories summarizes formulae for testing field measurements. An extensive bibliography is presented in addition to the section describing references cited in the body of the report. Finally, Appendix A describes the notation used in this report.

Selection Criteria

This report emphasizes theories for suspended sediment transport in or immediately adjacent to the surf zone in combined wave-current nearshore flows under conditions such that quasi-unidirectional currents do not dominate the combined flow.

The criteria used to select theories for further consideration are as follows:

- a. Theories must be valid within the surf zone.
- b. Theories must specifically predict suspended-sediment transport at a point; theories yielding only predictions of transport averaged over any spatial coordinate other than the vertical are excluded. Acceptable theories may thus require as input depth-averaged fluid and sediment quantities, but theories predicting only transport averaged over the width of the surf zone, for example, are excluded.
- c. Specifically excluded are formulations using only bed elevation measurements as input and the kinematic constraints of the sediment conservation equation to calculate spatial gradients in the sediment transport rate. Such formulations do not provide predictions of the sediment transport rate based on measured fluid-motion and grain-size parameters.

The comprehensive literature search focused primarily on theories presented in refereed journals and government reports, because they are readily available in most libraries and have been peer reviewed. However, a considerable sediment-transport literature exists outside this group, primarily in the form of conference proceedings, and these reports are included in the survey to the extent that such reports are available. Fortunately, there is considerable overlap between the refereed and so-called "gray" literature, so that essentially all useful transport formulae published in the English language (or translated to English from the original literature) are included here.

2 Theory

Theories for transport of suspended sediment fall into three broad categories: those based on explicit energy arguments; those based on the diffusion theory or modifications to it; and quasi-empirical predictors of sediment transport. With few exceptions, theories for suspended sediment transport in the surf zone are directly based on or are fundamentally related to theories first developed to describe steady unidirectional flows in fixed-bed channels. Thus, the original theories for unidirectional flow are occasionally referenced to clarify the derivations of surf zone transport theories.

Because the so-called "energetics" models require the measurement of far fewer quantities to predict transport in the surf zone, they are greatly favored in nearshore field studies. The following sub-sections outline the energy-based approach of Bagnold (1963; 1966), critically examine assumptions made in a number of energetics-based theories that extend Bagnold's approach, and list the limitations of those theories; then a similar approach is taken with the diffusion theories. Finally, two commonly used quasi-empirical predictors of sediment transport are critically examined. Particular emphasis is given to calibration constants and free parameters in the theories.

Energetics-Based Theories for Suspended-Sediment Transport

Energetics-based theories for suspended sediment transport following the assumptions of Bagnold (1963; 1966) have been proposed by numerous investigators. The form of the general theory and its assumptions are presented below, followed by a critical examination of the modifications to it for unsteady oscillatory flow proposed by Bowen (1980), Bailard (1981; 1982; 1987) and Roelvink and Stive (1989).

Bagnold (1966) derived relations for the transport of sediment as bed load and suspended load in unidirectional streams based on the assumption that a fixed fraction of the total stream power is expended moving bed load, and that a fixed fraction of the remaining available power is expended transporting suspended sediment. Bagnold (1966, p. I-4) defined bed load as "that part of

the load which is supported wholly by a solid-transmitted stress," and suspended load as "that part which is supported by a fluid-transmitted stress." Taking the total stream power ω as

$$\omega = \rho ghS\bar{u} \quad (1)$$

where

- ρ = fluid density
- g = gravitational acceleration
- h = flow depth
- S = energy slope
- \bar{u} = mean flow velocity

Bagnold assumed that the immersed-weight transport rate of suspended load is

$$i_s = \frac{e_s \bar{u}(1-e_b)}{W} \omega \quad (2)$$

where

- e_s = suspended-load transport efficiencies
- e_b = bed load
- W = sediment fall velocity¹

Unfortunately, there is an error in Bagnold's derivation of the suspended sediment efficiency e_s that appears to seriously compromise the theory. In Bagnold's Equation 14 (p. I-14), he mistakenly suggests that the momentum flux due to downward-directed momentum moving downward is opposite that due to upward-directed momentum moving upward, when in fact both have the same sign.

Despite its deficiencies, Bagnold and others have extended the energetics approach to predict sediment transport in unsteady oscillatory flows. For oscillatory flows, Bagnold (1963) proposed a similar relation for the total load:

$$i_{\theta} = K_B \omega \frac{u_{\theta}}{u_m} \quad (3)$$

¹ For convenience, symbols are listed in the notation (Appendix A).

where

- K_B = constant
- u_θ = current velocity in the θ direction
- u_m = maximum wave orbital velocity measured at the same distance above the bed as u_θ
- i_θ = transport in the θ direction

Although not considered further here, functionally similar expressions for the total load have been developed by many investigators. The following paragraphs outline and contrast the modifications to Bagnold's ideas proposed by Bowen (1980), Bailard (1981; 1982; 1987), and Roelvink and Stive (1989).

Common to each of the energetics-based theories are the following assumptions:

- a. The immersed sediment transport rate i is proportional to ω , the local rate of energy dissipation. Assuming that the shear stress τ is quadratic in the velocity u

$$\tau = \rho c_f u^2 \quad (4)$$

where c_f is the bed drag coefficient, and the rate of energy dissipation ω is assumed to be

$$\omega = \rho c_f |u|^3 \quad (5)$$

- b. Equations 4 and 5 assume zero phase difference between stress and velocity.
- c. The bathymetry is free of bed forms, and has parallel contours.
- d. Flow accelerations play no role in the sediment transport processes.
- e. The sediment grain-size distribution is completely characterized by a single constant fall velocity W , which is independent of concentration.
- f. There is no provision for initiation of sediment motion.
- g. Sediment transport responds instantaneously to changes in flow conditions.
- h. An implicit assumption is that the concentration of suspended sediment is sufficiently low that stratification effects can be neglected (e.g., Villaret and Trowbridge (1991)).

- i. Vertical fluid velocities are assumed to play no role in the depth-integrated transport process, beyond their obvious role in suspending sediment. There is mounting evidence (e.g. Bowen (1990), summary in Nielsen (1992) that vertical velocities can be important, particularly if sediment concentration decreases slowly with distance from the bed.

Generalizing the expression developed by Bailard (1981), the time-averaged immersed suspended-sediment transport rate at a point is

$$\langle \vec{\tau} \rangle = \rho c_f \frac{e_s}{W} \left[\langle |\vec{u}|^3 \vec{u} \rangle + K_1 + K_2 \langle |\vec{u}|^5 \rangle \hat{i} \right] \quad (6)$$

where angle brackets indicate time averaging, \vec{u} is the instantaneous fluid velocity vector, \hat{i} is the unit vector in the downslope direction, and the constants K_1 and K_2 are discussed below. For purposes of discussing proposed variations of Equation 6, the primitive equation (e.g., Guza and Thornton (1985)) for suspended-sediment transport in the cross-shore (x) direction in the case $K_1=0$ is

$$\langle i \rangle = \frac{e_s c_f \rho u^3 |u|}{W(1-K_2 u)} \quad (7)$$

Here u is the velocity component parallel to the local bed slope.

Bowen (1980)

Bowen adopted Bagnold's model as a simple starting point for developing models of onshore-offshore transport. Explicitly supposing the maximum orbital wave velocity u_m to dominate the total velocity

$$u = u_m \cos(\sigma t) + U_1 \quad (8)$$

where σ is the radial wave frequency, Bowen expanded Equation 8 and investigated several cases for various forms of the perturbation U_1 .

Both Bagnold and Bowen derived $K_1=0$ and $K_2=\beta/W$ (implicitly assuming $\beta \ll 1$, so that $\tan \beta \approx \beta$, where β = angle of bed slope). Bowen specifies temporal averaging over many wave periods.

Bailard (1981; 1982; 1987)

Bailard derived a slightly different form of Equation 6, keeping only the first two terms in the binomial expansion of Equation 7. Bailard's derivation gives $K_1=0$ and $K_2 = e_s \tan \beta / W$. As Bailard (1981, p. 10,952) notes, "this

difference arises because Bagnold assumed that the stream power contribution from the suspended sediment load contributes directly to the suspended sediment transport rate instead of through an efficiency factor..."

The possibility of "autosuspension" arises when the factor $(1-K_2u)$ in the denominator of Equation 7 approaches zero. The expansion leading to (6) is singular in this case. First noted by Knapp (1938), autosuspension refers to turbulent flows transporting suspended sediment in which the rate of energy input to the flow by the downslope motion of the sediment equals or exceeds the rate at which energy is expended by the flow to suspend the particles. In such cases, additional sediment can be suspended by the flow with no net energy input, and thus the concentration is limited only by sediment availability.

The models of Bailard and Bowen both admit the possibility of autosuspension, though the quantitative criteria differ. Bailard (1981) and Pantin (1979) predict autosuspension when

$$\tan\beta \geq \frac{W}{e_s u} \quad (9)$$

and Bagnold (1962) and Bowen (1980) predict autosuspension when

$$\tan\beta \geq \frac{W}{u} \quad (10)$$

Clearly such conditions can arise in the surf zone, and the viability of the autosuspension concept has been debated in the literature. Critical laboratory experiments by Southard and Mackintosh (1981) show that the Bagnold autosuspension criteria (Equation 10) is not valid. Their experiments, which do not test the more conservative criterion (Equation 9) proposed by Bailard and Pantin, strongly suggest that the energy balance in these flows is not merely a matter of comparing the energy input by the downslope motion of suspended particles and the energy expended to suspend the particles. That comparison ignores the changes induced by the presence of suspended particles on the turbulent structure of the flow; and perhaps of greater importance, does not include the effects of high suspended-sediment concentration on the boundary resistance. Turbulence is damped by density stratification at high concentrations, thus limiting the vertical transport of mass and momentum (McLean 1991). Thus boundary resistance can be significantly decreased as the suspended load increases, in turn reducing the ability of the flow to entrain more sediment into suspension. It is this balance between entrainment and deposition at the bed, Southard and Mackintosh argue, that governs the equilibrium concentration of sediment in the flow. Further discussion of the issues can be found in Parker (1982), Pantin (1982), Paola and Southard (1983), and Seymour (1986).

Roelvink and Stive (1989)

The theory proposed by Roelvink and Stive (RS) assumes $K_2 = 0$, and derives K_1 based on a one-equation model for turbulence produced by breaking waves. The overall goal of their theory is to incorporate models for a variety of cross-shore flows, such as asymmetric oscillatory flow, wave grouping-induced long-wave flow, breaking-induced turbulent flow, and momentum decay-induced undertow. The resulting model for the fluid flow, derived for cross-shore transport only, can be simplified and used for comparison with field data. In their model, the parameter K_1 is

$$K_1 = \beta_d \{ k_t [\exp(h/H_{rms}) - 1]^{-1} \}^{3/2} \quad (11)$$

where β_d is a dimensionless coefficient (assumed to be ≈ 1), H_{rms} = root-mean-square wave height, and k_t is the turbulent kinetic energy per unit mass

$$k_t = \frac{1}{2} [\langle u'^2 \rangle + \langle v'^2 \rangle + \langle w'^2 \rangle] \quad (12)$$

where primes indicate fluctuating velocity components. Although the RS model calculates k_t by an iterative solution of a system of equations, available field data may be used to determine k_t directly. Alternatively, the average dissipation ϵ_d per unit mass due to wave breaking might be approximated following Thornton and Guza (1986):

$$\epsilon_d = \frac{3}{16} \sqrt{\pi} g \frac{B^3}{\gamma^4 h^5} f_p H_{rms}^7 \quad (13)$$

where f_p is the peak frequency, γ is an empirically determined ratio of root-mean-square wave height H_{rms} to the water depth h in the surf zone (Thornton and Guza 1983), and is typically about 0.4 ± 0.1 . The coefficient B accounts for differences in wave breaking; it is less than one for spilling breakers and near unity for plunging breakers (Thornton and Guza 1986). Then, assuming a balance between the dissipation ϵ_d and the creation of turbulent kinetic energy gives

$$k_t^{3/2} = \epsilon_d \quad (14)$$

which supplies all the information necessary to determine K_1 .

Humiston (1993)

Following Guza and Thornton (1985), Humiston modeled contributions of infragravity and incident waves and quasi-steady currents to cross-shore transport of both bed load and suspended load. The total velocity is decomposed into quasi-steady and oscillatory components

$$\vec{u}_t = (\bar{u} + \tilde{u}) \hat{i} + (\bar{v} + \tilde{v}) \hat{j} \quad (15)$$

where overbars indicate the quasi-steady quantities, tildes indicate oscillatory ones, and \hat{i} and \hat{j} are unit vectors in the on-offshore and alongshore directions.

The oscillatory terms are further expanded into infragravity \tilde{u}_i ($f < 0.05$ Hz) and incident \tilde{u}_s ($f > 0.05$) components such that

$$\tilde{u} = \tilde{u}_i + \tilde{u}_s \quad (16)$$

and

$$\tilde{v} = \tilde{v}_i + \tilde{v}_s \quad (17)$$

The magnitude of the total velocity is then

$$|\vec{u}_t| = [\bar{u}^2 + \bar{v}^2 + \tilde{u}^2 + \tilde{v}^2 + 2(\bar{u}\tilde{u} + \bar{v}\tilde{v})]^{1/2} \quad (18)$$

This decomposition of the oscillatory flow velocities may be useful in comparing model outputs with field measurements.

Bed friction and suspended sediment efficiency factors

The bed friction and suspended sediment efficiency factors are two important parameters in the energetics-based theories. Although both are assumed constant in the theories presented above, it is likely that the bed friction factor is a complex function of fluid-motion parameters, in particular, the properties of the bed-load layer and any small-scale bed roughness generated by the bed-load process. The choice of suspended sediment efficiency factor lacks theoretical guidance to indicate its value, and must be determined by calibration. The following discussion focuses on Bailard's studies, which typically form the basis for the choice of constants in other investigations.

Bailard (1981) determined the suspended sediment efficiency factor using selected data from laboratory and field experiments. He determined $e_s = 0.025$ (as well as the bed-load efficiency factor, the bed friction factor, and a number of other parameters) from measured estimates of total longshore transport and velocity using an iterative scheme from Ostendorf and Madsen (1979). Estimated values of the parameters are not independent, and error analysis is difficult. Bailard (1987, p. 339) used $e_s = 0.035$ for field data from Leadbetter and Torrey Pines Beaches as part of the nearshore sediment transport study. Other investigators have adopted Bagnold's (1966) estimate $e_s = 0.015$ for unidirectional stream flow. Since the transport rate is directly proportional to e_s , errors of 100 percent or more may be expected in uncalibrated application of Equation 6 to field measurements due to errors in estimating e_s alone.

The measured values of c_f in the experiments Bailard (1981) used to determine e_s , range from 0.013 to 0.017 for the laboratory experiments; for the three Silver Strand field experiments (see Komar (1969) for original data) used in the analysis, c_f ranged from 0.0026 to 0.014. It should be noted that the values for c_f presented in Bailard's Table 2 (p. 10,951) are inconsistent with his Equations 42 and 43 (p. 10,946) using $\Gamma = 0.13$ and values for other parameters from his Table 2. There is no discussion of the value adopted for c_f in the calculations in the paper, although subsequent papers (Bailard (1982), p. 1424) cite a value of $c_f = 0.005$ based on Komar's (1969) Silver Strand data.

Because the bed friction factor c_f is an integral part of many longshore current models, there has been considerably more study of c_f than e_s . Shemdin et al. (1978) compiled values of c_f for various field studies of wave dissipation, and found a range of 0.005 to 0.3. Thornton and Guza (1986) determined c_f using different longshore models; for a linear bed shear stress model (Equation 14, p. 1167) they found the optimal $c_f = 0.009 \pm 10.001$, while for the nonlinear model (Equations 22 and 23, p. 1168) the best-fit $c_f = 0.006 \pm 10.0007$, significantly less than for the linear model. Their linear model corresponds to the quadratic shear stress model Equation 4 assumed in the energetics-based transport models. Thus, uncalibrated application of Equation 6 and its variants may introduce uncertainties of 100 percent and more into transport estimates due to errors in c_f .

Diffusion-Based Theories for Suspended-Sediment Transport

Several theoretical approaches to suspended sediment transport seek to calculate transport based on a detailed picture of near-bed fluid motion, in particular, the computation of the boundary shear stress and the assumption that fluid turbulence diffuses sediment according to a Fickian diffusion law. The assumption of Fickian diffusion is not the only one possible, but alternatives to it (e.g., McTigue (1983)) have not been used in the context of nearshore transport and thus are not considered further here.

Rouse (1937) derived a diffusion-based theory for suspended sediment transport in steady, uniform unidirectional flow, which forms the basis for theories describing transport in unsteady, combined flows in the nearshore. The governing convection-diffusion equation for the volume concentration of sediment N is

$$\frac{\partial N}{\partial t} = W \frac{\partial N}{\partial z} + \frac{\partial}{\partial z} \left[v_s \frac{\partial N}{\partial z} \right] \quad (19)$$

where ν_s is the sediment diffusivity, often equated to the fluid eddy viscosity, and diffusion and advection in the x and y directions have been neglected. For steady uniform flow in a channel, the vertical distribution of suspended sediment is then

$$N = N_0 \left[\frac{h-z}{z} \frac{z_0}{h-z_0} \right]^R \quad (20)$$

The Rouse number R is

$$R = \frac{W}{c_r \kappa u_*} \quad (21)$$

where c_r is an empirically determined constant of proportionality between the sediment diffusivity and the fluid eddy viscosity (often assumed to be unity), κ is von Karman's constant, and $u_* = (\tau_b / \rho)^{1/2}$ is the friction velocity. The derivation of Equation 19 assumes a law-of-the-wall velocity profile; application of it requires specification of a boundary condition at $z = z_0$. Typical extensions to the Rouse formulation for unsteady flows include a time-varying and/or vertically varying eddy viscosity, and a bed-shear stress relation for the reference concentration N_0 .

Kennedy and Locher (1972) and Smith (1977) present thorough discussions of the diffusion-based theories and their application to both oscillatory and unidirectional flows. Grant and Madsen (1979) use an eddy-diffusivity closure scheme to couple equations for conservation of fluid momentum and sediment mass to describe combined wave-current flows on the continental shelf. They solve the model equations using an iterative numerical technique. Glenn and Grant (1987) extended the work of Grant and Madsen (1979) to include stratification effects. Wikramanayake and Madsen (1992) used new relations for the reference concentration at the bed in an otherwise similar approach to suspended sediment transport under unbroken waves.

Diffusion-based theories have been extended to treat several special cases of sediment transport in the surf zone, but there have been no theories developed to treat the general case of combined wave-current flow that have been reduced to a single formula for comparison with field measurements; the analyses typically result in systems of coupled nonlinear equations that must be solved numerically. Major difficulties in applying such theories to field data include specification of initial and boundary conditions with sufficient detail to ensure unique solutions to the equations. A brief review of diffusion-based models for suspended sediment transport in the surf zone is presented below; however, none of the theories meet the selection criteria and thus are not included in Table 1.

In general, the instantaneous rate of suspended sediment transport is given by

$$\int \bar{u} N dz \quad (22)$$

where \bar{u} is the instantaneous fluid velocity, and the integral is taken from the bed to the free surface. Theories presented below use various approaches to evaluate the vertical distributions of the diffusivity ν_s in Equation 19 and \bar{u} in Equation 22, and to decompose \bar{u} into mean and fluctuating components due to currents, waves, and turbulence. Implicit in all the following formulas, unless otherwise noted, are the following assumptions:

- a. The horizontal velocity of the sediment particles is equal to the horizontal fluid velocity.
- b. Flow accelerations play no explicit role in the sediment transport processes.
- c. The concentration of suspended sediment is sufficiently low that stratification effects can be neglected.

As can be seen, assumptions for the diffusion-based theories are far fewer than for the energetics-based models, and means to rationally extend the theories are typically available, although often analytically intractable.

Dally and Dean (1984)

The two-layer model proposed by Dally and Dean for cross-shore suspended sediment transport assumes that sediment motion occurs by two mechanisms. In the near-bottom layer, each grain is transported a small distance before redepositing on the bed. Derivation of this "first-order contribution," in their terminology, assumes linear wave theory to predict the mean horizontal distance traveled by a grain in one wave period. The second transport mechanism is a mean flow (derived from radiation stress and conservation of mass requirements) that operates in both the near-bed and upper layers. The sum of these sediment velocity contributions is multiplied by the sediment concentration profile to determine the vertical profile of suspended sediment transport using a finite-difference scheme. The concentration profile is modified from Rouse (1937) to include a contribution to the shear velocity due to wave-breaking-induced turbulence. Several parameters in the theory are not specified by Dally and Dean, and thus quantitative comparison of their theory with field measurements is not possible.

Deigaard, Fredsoe, and Hedegaard (1986)

Using the analogy of a turbulent bore to describe a spilling breaker, Deigaard, Fredsoe, and Hedegaard (1986) solve numerically a one-equation model describing the transport and diffusion of turbulent kinetic energy in the

surf zone. The total eddy viscosity comprises contributions due to turbulence and to the production of energy in the combined wave-current motion. The latter contribution is calculated according to the theory of Fredsoe, Anderson, and Silberg (1985). Finally, the suspended sediment transport is calculated according to Engelund and Fredsoe (1976).

Semi-Empirical Models for Suspended Sediment Transport

Given the difficulty in predicting suspended sediment transport in the nearshore from first principles, several engineering-oriented approaches have made extensive use of field data from evolving beaches and from large-scale laboratory studies to parameterize transport processes. The semi-empirical or schematic theories described below are based on the assumption that an equilibrium profile exists for any constant wave climate. Although that assumption is currently the subject of vigorous study, the schematic approaches are a practical, albeit crude, means of predicting sediment transport, particularly when detailed fluid-motion data are lacking and some a priori knowledge of the typical beach profile is available.

Larson and Kraus (1989)

Founded on considerable field and laboratory data, the SBEACH model developed by Larson and Kraus (1989) (hereafter referred to as "LK") extends the energy dissipation models proposed by Kriebel and Dean (1985) and Kriebel (1986) to predict total net sediment transport in the surf zone and foreshore. These models are designed to make predictions about "large-scale profile features on intervals of tens of minutes" (LK, p.139). Thus they differ fundamentally in purpose from theories described above, which predict transport on a wave-by-wave basis. These models make the following assumptions:

- a. Beach profile change, and thus total net sediment transport, is mainly governed by breaking of short-period waves having periods in the approximate range of 3-20 s (LK, p.12). Thus infragravity waves are explicitly assumed to have little effect on sediment transport and resulting profile evolution.
- b. An equilibrium profile exists such that the energy dissipation per unit volume is uniform across the surf zone (Dean 1977). Dean's development of this hypothesis assumes linear wave theory, a constant ratio of wave height to water depth within the surf zone, and linear and parallel bottom contours to arrive at a characteristic equilibrium profile shape

$$h = Ax^{\frac{2}{3}} \quad (23)$$

where A , the profile shape parameter, is a function of particle size or fall velocity and x is distance offshore. Departures from this equilibrium profile provide the driving mechanism for sediment transport.

- c. Waves are normally incident, and only cross-shore transport is predicted.
- d. The direction of transport (i.e. onshore or offshore) is determined by an empirical criterion that differentiates between bar growth (offshore transport), and berm growth (onshore transport).
- e. The magnitude of the total net transport at a point is directly proportional to the difference between the energy dissipation rate per unit volume estimated from field measurements and the equilibrium dissipation rate determined according to Dean's (1977) hypothesis. The transport formula proposed by LK (p. 167) is

$$\langle i \rangle = \text{sgn} \left\{ M \left[\frac{\langle H_0 \rangle}{WT} \right]^3 - \frac{2\pi \langle H_0 \rangle}{gT^2} \right\} (\rho_s - \rho) gK \left[E - E_{eq} + \frac{\epsilon_\beta}{K} \frac{dh}{dx} \right] \quad (24)$$

when

$$E > E_{eq} - \frac{\epsilon_\beta}{K} \frac{dh}{dx} \quad (25)$$

and $\langle i \rangle = 0$ otherwise. The sign or direction of transport (i.e., sgn) is determined by the quantity in curly brackets, based on an empirical criterion that differentiates between bar growth (offshore transport in the direction of increasing coordinate x) and berm growth (onshore transport). The quantity dh/dx is the bed slope, H_0 is the deepwater wave height, W is the sediment fall velocity, T is the wave period determined from the spectral frequency peak f_p , $M=0.0007$ is an empirical constant and ρ_s is sediment density. The magnitude of transport is determined from the quantity in the right-most square brackets, in which E is the energy dissipation rate per unit volume calculated according to assumptions discussed below, E_{eq} is the equilibrium energy dissipation rate, and ϵ_β is a constant. The term involving the beach slope $\epsilon_\beta h/dx$ is incorporated primarily to improve the numerical stability of the model (LK, p. 168). The value of the transport rate coefficient K is determined from experimental and field measurements, and is discussed in more detail below. The erosion-only model of Kriebel and Dean (1985) and Kriebel (1986) is a special case of Equation 24 in which transport is assumed to be directed offshore only, and the term involving the beach slope dh/dx is neglected.

The general form of Equation 24 implies an interesting physical picture of sediment transport along the cross-shore profile. According to the criterion in curly brackets, determined from quantities measured well outside the surf zone, sediment “is transported offshore or onshore along the full length of the active profile at a specific instant in time” (LK, p. 166). As noted by LK (p. 166), this formulation is less likely to correctly predict the actual direction of transport as the beach approaches equilibrium, where small departures from equilibrium may create large qualitative changes in sediment transport (i.e., change the direction of transport). Under conditions of relatively great profile disequilibrium, this deficiency in the model is thought to be less important.

The derivation of expressions for E and E_{eq} follows Dean (1977, Appendix III), assuming linear wave theory:

$$E = \frac{1}{h} \frac{d}{dx} \left[\frac{1}{8} \rho g H_s^2 \sqrt{gh} \right] \quad (26)$$

where H_s is the mean significant wave height. A useful form for calculating E from field measurements is

$$E = \frac{\rho g \frac{3}{2} d(H_s^2 h)}{8h \frac{3}{2}} \quad (27)$$

although discretization of Equation 27 using less than three relatively closely spaced measurement sites will yield predictions of transport at a point interpolated between actual measurement points.

The expression for E_{eq} is (LK, p. 168)

$$E_{eq} = \frac{5}{24} \rho g \frac{3}{2} \gamma_b^2 A \frac{3}{2} \quad (28)$$

where γ_b is the breaker index, the ratio between wave height and water depth at breaking. Equation 28 is derived by substituting $\gamma_b h$ for H_s in Equation 26 and differentiating with respect to x to obtain

$$E_{eq} dx = \frac{5}{16} \rho g \frac{3}{2} \gamma_b^2 h \frac{1}{2} dh \quad (29)$$

which can be integrated to give Equation 23.

The profile shape parameter A is then

$$A = \frac{24}{5} \frac{E_{eq}^{\frac{2}{3}}}{\rho g^{\frac{2}{3}} \gamma^2} \quad (30)$$

which can in turn be solved for E_{eq} .

Dean (1987) proposed an empirical dimensional formula for determining A as a function of settling velocity W

$$A = 0.067W^{0.44} \quad (31)$$

in which A has units of meters^{1/3} when the settling velocity W is expressed in cm s⁻¹. The fit to the data used by Dean (1987, p. 11) appears good for $D_{50} > 1$ mm, and less good for smaller grains likely to be transported in suspension. It is not clear whether LK use Equation 31 to determine A or the earlier relationship proposed by Moore (1982).

SBEACH parameters

Various parameters for SBEACH have been determined for laboratory and field application. The particular choice of wave height, for example, depends on the intended application. This section summarizes and discusses parameters and measurements relevant to field application of SBEACH.

The recommended value of the transport rate coefficient K appearing in Equation 24 was determined for both laboratory and field situations by minimizing the sum of squares of deviations between measured and predicted profile elevations. Seven erosional (bar-forming) profiles generated in large wave laboratory facilities were used to determine an optimal value for K of $1.6 \cdot 10^{-6} \text{ m}^4 \text{ N}^{-1}$; in the field, a value of $K=0.7 \cdot 10^{-6} \text{ m}^4 \text{ N}^{-1}$ minimized the discrepancy between measured and calculated profiles. Moore (1982) determined a value of $K=2.2 \cdot 10^{-6} \text{ m}^4 \text{ N}^{-1}$ using laboratory and field data in a similar model (no explicit term proportional to dh/dx). Intercomparison between SBEACH and the model of Kriebel (1986) produced an optimal $K=8.7 \cdot 10^{-6} \text{ m}^4 \text{ N}^{-1}$ for the Kriebel model. Because it is not possible to relate the predicted transport rate to any physically measureable quantity, finding an optimal calibration procedure for K is difficult. Finally, the breaker index γ_b is set equal to unity for field application (LK, p. 207). Note that γ_b differs from γ , the ratio of wave height to water depth across the surf zone (Thornton and Guza 1983).

Ackers and White (1973)

The semi-empirical sediment transport model of Ackers and White (1973) was developed for steady, uniform open-channel flows, and is considered here because it is widely used in a variety of applications. The model describes total sediment transport in terms of three dimensionless groups related to the size, mobility, and transport of grains having diameters greater than 0.04 mm. Nearly 1,000 flume experiments using well-sorted sediment in steady, uniform flows having depths up to 0.4 m form the empirical basis for the model. A single test of the model under a quasi-unidirectional flow regime was performed during one tidal cycle in an estuary (p. 2053):

... theoretical predictions appear to exaggerate the net transport in a landward direction. This is probably a result of the asymmetrical nature of the ebb/flood cycle and there is clearly a need for further investigation when the flow is time-dependent.

Use of the Ackers and White formulation is thus not recommended for nearshore oscillatory flows. The following sections outline the procedure for computing sediment transport of fine grains in suspension. A dimensionless grain diameter D_* , mobility parameter F_* , and transport parameter G_* are calculated as follows:

The dimensionless grain diameter D_* is

$$D_* = D \left[\frac{g(\rho_s - \rho)}{\rho \nu^2} \right]^{1/3} \quad (32)$$

where D is the medium grain size and ν is the kinematic viscosity. Ancillary parameters n , A_g , C_g , and m are empirically derived functions of D_* :

$$n = 1 - 0.56 \log D_* \quad (33)$$

$$A_g = 0.23 D_*^{-1/2} + 0.14 \quad (34)$$

$$\log C_g = 2.86 \log D_* - (\log D_*)^2 - 3.53 \quad (35)$$

$$m = 9.66 D_*^{-1} + 1.34 \quad (36)$$

Taking $n \approx 1$ for fine suspended sediments, the mobility parameter F_* is simply the square root of the Shield's parameter θ

$$F_* = \frac{u_*}{[gD(\rho_s - \rho)]^{1/2}} = \theta^{1/2} \quad (37)$$

and the transport parameter G_* is then

$$G_* = C_g \left[\frac{F_*}{A_g} - 1 \right]^m \quad (38)$$

Ackers and White formulate the sediment flux in terms of the sediment concentration in parts per million by weight of fluid flux, and thus the immersed sediment transport rate is

$$\langle i \rangle = 10^{-6} \frac{\rho_s - \rho}{\rho_s} C_s \left(\frac{F_*}{A_g} - 1 \right)^m \left(\frac{\rho_s D \bar{u}}{\rho h u_*} \right) \langle \rho \bar{u} h \rangle \quad (39)$$

where \bar{u} is the depth-averaged velocity, and the various factors of h , ρ and ρ_s have been left unsimplified for clarity. For field application, the shear velocity u_* in Equation 39 might be computed using Equation 4 and a suitable choice for c_f .

Table 1
Transport Formulae

Bowen (1980)¹
$$\langle \bar{\tau} \rangle = \rho c_f \frac{e_s}{W} \left[\langle |\bar{u}|^3 \bar{u} \rangle + \frac{\beta}{W} \langle |\bar{u}|^5 \rangle \hat{i} \right]$$

Bailard (1981)²
$$\langle \bar{\tau} \rangle = \rho c_f \frac{e_s}{W} \left[\langle |\bar{u}|^3 \bar{u} \rangle + \frac{e_s \tan \beta}{W} \langle |\bar{u}|^5 \rangle \hat{i} \right]$$

Roelvink and Stive (1989) (cross-shore transport only)

$$\langle i \rangle = \rho c_f \frac{e_s}{W} \left[\langle |\bar{u}|^3 \bar{u} \rangle + K_1 \right]$$

where
$$K_1 = \beta_d \{ k_t [\exp(h/H_{rms}) - 1]^{-1} \}^{\frac{3}{2}}$$

Larson and Kraus (1989) (cross-shore transport only)

$$\langle i \rangle = \text{sgn} \left\{ M \left[\frac{\langle H_0 \rangle}{WT} \right]^3 - \frac{2\pi \langle H_0 \rangle}{gT^2} \right\} (\rho_s - \rho) gK \left[E - E_{eq} + \frac{\epsilon_\beta}{K} \frac{dh}{dx} \right]$$

when $E > E_{eq} - \frac{\epsilon_\beta}{K} \frac{dh}{dx}$, and zero otherwise.

Ackers and White (1973)

$$\langle i \rangle = 10^{-6} \frac{\rho_s - \rho}{\rho_s} C_g \left(\frac{F_*}{A_g} - 1 \right)^m \left(\frac{\rho_s D \bar{u}}{\rho h u_*} \right) (\rho \bar{u} h)$$

¹ Bagnold (1963) is functionally equivalent, but not elaborated in the same detail.

² Humiston (1993) follows Bailard (1981).

References

- Ackers, P., and White, W. R. (1973). "Sediment transport: New approach and analysis." *Proc. Hydraulics Div., American Society of Civil Engineers* 99 (HY11), 2041-2060.
- Bagnold, R. A. (1962). "Auto-suspension of transported sediment; turbidity currents." *Proc. Roy. Soc. London, A* 265, 315-319.
- _____. (1963). "Mechanics of marine sedimentation." *The sea*. M. N. Hill, ed., Interscience, New York, 507-528.
- _____. (1966). "An approach to the sediment transport problem from general physics," U. S. Geological Survey Professional Paper 422 (I), 1-37.
- Bailard, J. (1981). "An energetics total load sediment transport model for a plane sloping beach," *Journal of Geophysical Research* 86 (C11), 10938-10954.
- Bailard, J. A. (1982). "Modelling on-offshore sediment transport in the surfzone." *18th International Conference on Coastal Engineering*, 1419-1438.
- _____. (1987). "Surfzone wave velocity moments." *Conference on Coastal Hydrodynamics*, American Society of Civil Engineers, 328-342.
- Bowen, A. J. (1980). "Simple models of nearshore sedimentation; beach profiles and longshore bars." *The coastline of Canada*. Geological Survey of Canada Paper 80-10. S. B. McCann, ed., 1-11.
- _____. (1990). "On the kinematics of a sediment suspension," *EOS, Trans. AGU* 71 (43), 1369.
- Dally, W. R., and Dean, R.G. (1984). "Suspended sediment transport and beach profile evolution," *Journal of Waterway, Port, Coastal and Ocean Engineering* 110 (1), 15-33.

- Dean, R. G. (1977). "Equilibrium beach profiles: U.S. Atlantic and Gulf Coasts," University of Delaware, Dept. of Civil Engineering Ocean Engineering Report 12.
- _____. (1987). "Coastal sediment processes: Toward engineering solutions." *Coastal Sediments '87*, N. C. Kraus, ed., American Society of Civil Engineers, 1-24.
- Deigaard, R., Fredsoe, J., and Hedegaard, I. B. (1986). "Suspended sediment in the surf zone," *Journal of Waterway, Port, Coastal and Ocean Engineering* 112 (1), 115-128.
- Engelund, F., and Fredsoe, J. (1976). "A sediment transport model for straight alluvial channels," *Nordic Hydrology* 7, 293-306.
- Fredsoe, J., Anderson, O. H., and Silberg, S. (1985). "Distribution of suspended sediment in large waves," *Journal of Waterway, Port, Coastal and Ocean Engineering* 111 (61), 1041-1059.
- Glenn, S. M., and Grant, W. D. (1987). "A suspended sediment stratification correction for combined wave and current flows," *Journal of Geophysical Research* 92 (C8), 8244-8264.
- Grant, W. D., and Madsen, O. S. (1979). "Combined wave and current interaction with a rough bottom," *Journal of Geophysical Research* 84, 1979-1808.
- Guza, R. T., and Thornton, E. B. (1985). "Velocity moments in nearshore," *Journal of Waterway, Port, Coastal and Ocean Engineering* 111 (2), 235-256.
- Humiston, R. T. (1993). "Cross-shore sediment transport on a naturally barred beach," M.S. thesis, Naval Postgraduate School.
- Kennedy, J. F., and Locher, F. A. (1972). "Sediment suspension by water waves." *Waves on beaches*. R. E. Meyer, ed., Academic Press, New York, 249-298.
- Knapp, R. T. (1938). "Energy-balance in stream flows carrying suspended load." *Transactions, American Geophysical Union*, 19, 501-505.
- Komar, P. D. (1969). "The longshore transport of sand on beaches," Ph.D. diss., University of California, San Diego.
- Kriebel, D. L. (1986). "Verification study of a dune erosion model," *Shore and Beach* 54 (3), 13-21.

- Kriebel, D. L., and Dean, R. G. (1985). "Numerical simulation of time-dependent beach and dune erosion," *Coastal Engineering* 9 (3), 221-245.
- Larson, M., and Kraus, N. C. (1989). "SBEACH: Numerical model for simulating storm-induced beach change; Report 1, Empirical foundation and model development," U. S. Army Engineer Waterways Experiment Station, Vicksburg, MS.
- McLean, S. R. (1991). "Depth-integrated suspended-load calculations," *Journal of Hydraulic Engineering* 117 (11), 1440-1458.
- McTigue, D. F. (1983). "Mixture theory for turbulent diffusion of heavy particles." *Theory of dispersed multiphase flow*. Academic Press, 227-250.
- Moore, B. D. (1982). "Beach profile evolution in response to changes in water level and wave height," M.S. thesis, University of Delaware.
- Nielsen, P. (1992). *Coastal bottom boundary layers and sediment transport*. World Scientific, Singapore.
- Ostendorf, D. W., and Madsen, O. S. (1979). "An analysis of longshore currents and associated sediment transport in the surf zone," R. M. Parsons Laboratory, Massachusetts Institute of Technology Technical Report 241, 84-96.
- Pantin, H. M. (1979). "Interaction between velocity and effective density in turbidity flow: Phase-plane analysis, with criteria for autosuspension," *Marine Geology* 31, 59-99.
- _____. (1982). "Comments on: Experimental test of autosuspension," *Earth Surface Processes and Landforms* 7, 503-505.
- Paola, C., and Southard, J. B. (1983). "Autosuspension and the energetics of two-phase flows: Reply to comments on Experimental test of autosuspension by J.B Southard and M. E. Mackintosh," *Earth Surface Processes and Landforms* 8, 273-279.
- Parker, G. (1982). "Discussion of: Experimental test of autosuspension (Southard and Mackintosh, 1981)," *Earth Surface Processes and Landforms* 7, 507-510.
- Roelvink, J. A., and Stive, M. J. F. (1989). "Bar-generating cross-shore flow mechanisms on a beach," *Journal of Geophysical Research* 94 (C4), 4785-4800.
- Rouse, H. (1937). "Modern conceptions of the mechanics of turbulence," *Transactions, American Society of Civil Engineers* 102, 436-505.

- Seymour, R. J. (1986). "Nearshore auto-suspending turbidity flows," *Ocean Engineering* 13, 435-447.
- Shemdin, O. H., Hasselman, K., Hsiao, S. V., and Herterich, K. (1978). "Nonlinear and linear bottom interaction effects in shallow water." *Turbulence fluxes through the sea surface, wave dynamics and prediction.* A. Favre and K. Hasselman, ed., Plenum, New York, 347-372.
- Smith, J. D. (1977). "Modeling of sediment transport on continental shelves." *The sea.* E. D. Goldberg et al., eds., John Wiley and Sons, New York, 539-577.
- Southard, J. B., and Mackintosh, M. E. (1981). "Experimental test of autosuspension," *Earth Surface Processes and Landforms* 6, 103-111.
- Thornton, E. B., and Guza, R. T. (1983). "Transformation of wave height distribution," *Journal of Geophysical Research* 88, 5925-5938.
- _____. (1986). "Surf zone longshore currents and random waves: field data and models," *Journal of Physical Oceanography* 16, 1165-1178.
- Villaret, C., and Trowbridge, J. H. (1991). "Effects of stratification by suspended sediments on turbulent shear flows," *Journal of Geophysical Research* 96 (C6), 10659-10680.
- Wikramanayake, P. N., and Madsen, O. S. (1992). "Calculation of suspended sediment transport by combined wave-current flows," Contract Report DRP-94-7, U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS.

Bibliography

- Abdelrahman, M. A., and Bedford, K. W. (1990). "Similarity analysis of the temporal variation of suspended sediment profiles," *Journal of Geophysical Research* 95 (C9), 16217-16227.
- Annandale, G. W. et al. (1990). "Uncertainty in suspended sediment transport curves - discussion," *Journal of Hydraulic Engineering-ASCE* 116 (1), 140-151.
- Antsyferov, S. M., and Kosyan, R. D. (1990). "Study of suspended sediment distribution in the coastal zone," *Coast Eng.* 14 (2), 147-172.
- Aziz, N. M., Prasad, S. N., and Bhattacharya, S. K. (1992). "Suspended sediment concentration profiles using conservation laws," *Journal of Hydraulic Research* 30 (4), 539-554.
- Bagnold, R. A. (1968). "Deposition in the process of hydraulic transport," *Sedimentology* 10, 45-56.
- Bakker, W. T. (1974). "Sand concentration in an oscillatory flow." *14th Coastal Engineering Conference*. American Society of Civil Engineers, 1129-1148.
- Bakker, W. T., and Doorn, T. H. (1978). "Near bottom velocities in waves with a current." *16th Coastal Engineering Conference*. American Society of Civil Engineers, 1394-1413.
- Beach, R. A., and Sternberg, R. W. (1988). "Suspended sediment transport in the surf zone - response to infragravity motion," *Marine Geology* 80, 61-79.
- _____. (1992). "Suspended sediment transport in the surf zone - response to incident wave and longshore current interaction," *Marine Geology* 108, 275-294.
- Celik, I., and Rodi, W. (1991). "Suspended sediment-transport capacity for open channel flow," *Journal Of Hydraulic Engineering-ASCE* 117 (2), 191-204.

- Celik, I., and Rodi, W. (1992). "Suspended sediment-transport capacity for open channel flow - closure," *Journal of Hydraulic Engineering-ASCE* 118 (5), 825-827.
- Cheng, K. J. (1984). "Bottom boundary condition for nonequilibrium transport of sediment," *Journal of Geophysical Research* 89 (C5), 8209-8214.
- Church, J. C., and Thornton, E. B. (1993). "Effects of breaking wave induced turbulence within a longshore current model," *Journal of Coastal Engineering*, in press.
- Crawford, C. G. (1991). "Estimation of suspended-sediment rating curves and mean suspended-sediment loads," *Journal of Hydrology* 129 (1-4), 331-348.
- Curto, L. A. (1985). "On the motion of very small bodies in water waves," *Journal of Geophysical Research* 90 (C1), 1127-1132.
- Dean, R. G. (1973). "Heuristic models of sand transport in the surfzone," *Conference on Engineering Dynamics in the Surf Zone*.
- Dean, R. G., and Dalrymple, R. A. (1991). *Water wave mechanics for engineers and scientists*. World Scientific, Singapore.
- Deigaard, R., and Fredsoe, J. (1989). "Shear stress distribution in dissipative water waves," *Coastal Engineering* 13 (4), 357-378.
- Devantier, B. A., and Narayanaswamy, R. (1989). "A suspended sediment flow model for high solids concentration using higher order turbulence closure," *Advances In Water Resources* 12 (1), 46-52.
- Doering, J. C., and Bowen, A. J. (1988). "Wave induced flow and nearshore suspended sediment." *21st Coastal Engineering Conference*. B. L. Edge, ed., American Society of Civil Engineers, 1452-1463.
- Eidsvik, K. J., and Utnes, T. (1991). "A model for sediment re-entrainment and transport in shallow basin flows," *Coastal Eng.* 15, 247-256.
- Fredsoe, J. (1984). "Turbulent boundary layer in wave-current motion," *Journal of Hydraulic Engineering* 110 (61), 1103-1120.
- Fredsoe, J., and Deigaard, R. (1992). *Mechanics of coastal sediment transport*. World Scientific, Singapore.
- Galappatti, G., and Vreugdenhil, C. B. (1985). "A depth-integrated model for suspended sediment transport," *Journal of Hydraulic Research* 23 (4), 359-377.
- Gross, T. F., and Dade, W. B. (1991). "Suspended sediment storm modeling," *Marine Geology* 99 (3-4), 343-360.

- Hagatun, K., and Eidsvik, K. J. (1986). "Oscillating turbulent boundary layers with suspended sediment," *Journal of Geophysical Research* 91 (C11), 13045-13055.
- Hattori, M. (1969). "The mechanics of suspended sediment due to standing waves," *Coastal Engineering in Japan* 12, 69-81.
- _____. (1974). "Delay distance in suspended sediment transport," *Coastal Engineering Conference*, 63, 1086-1095.
- Hay, A. E., and Bowen, A. J. (1993). "Spatially correlated depth changes in the nearshore zone during autumn storms," *Journal of Geophysical Research* 98 (C7), 12,387-12,404.
- Hom-ma, M., Horikawa, K., and Kajima, R. (1965). "A study of suspended sediment due to wave action," *Coastal Engineering in Japan*, 8.
- Hunt, J. N. (1954). "The turbulent transport of suspended sediment in open channels." *Proceedings of the Royal Society of London. Series A*, 224, 322-335.
- Hwang, P. A. (1985). "Comment on ' On the motion of suspended sand particles'," *Journal of Geophysical Research* 90 (C2), 3253-3254.
- Ingram, J. J., Abt, S. R., and Richardson, E. V. (1991). "Sediment discharge computation using point-sampled suspended-sediment data," *Journal Of Hydraulic Engineering-ASCE* 117 (6), 758-773.
- Johns, B., Chesher, T. J., and Soulsby, R. L. (1990). "The modelling of sandwave evolution resulting from suspended and bed load transport of sediment," *Journal Of Hydraulic Research* 28 (3), 355-374.
- Katopodi, I., and Ribberink, J. S. (1992). "Quasi-3D modelling of suspended sediment transport by currents and waves," *Coastal Engineering* 18, 83-110.
- Kineke, G. C., and Sternberg, R. W. (1989). "The effect of particle settling velocity on computed suspended sediment concentration profiles," *Marine Geology* 90 (3), 159-174.
- Kriebel, D. L. (1982). "Beach and dune response to hurricanes," M.S. thesis, University of Delaware.
- Lemke, K. A. (1991). "Transfer function models of suspended sediment concentration," *Water Resources Research* 27 (3), 293-305.

- Lyne, V. D., Butman, B., and Grant, W. D. (1990). "Sediment movement along the United States east coast continental shelf; 2, Modelling suspended sediment concentration and transport rate during storms," *Continental Shelf Research* 10 (5), 429-460.
- Madsen, O. S., and Grant, W. D. (1976). "Quantitative description of sediment transport by waves." *15th Coastal Engineering Conference, American Society of Civil Engineers*, 1093-1112.
- McLean, S. R. (1990). "Modelling sediment suspension under waves," *EOS, Trans., AGU* 71 (43), 1369.
- _____. (1992). "On the calculation of suspended load for noncohesive sediments," *Journal of Geophysical Research* 97 (C4), 5759-5770.
- Middleton, G. V., and Southard, J. B. (1984). *Mechanics of sediment movement*. Tulsa, OK, SEPM.
- Nadaoka, K., Yagi, H., and Kamata, H. (1991). "A simple quasi-3-D model of suspended sediment transport in a nonequilibrium state," *Coastal Engineering* 15, 459-474.
- Nielsen, P. (1984). "On the motion of suspended sand particles," *Journal of Geophysical Research* 89 (C1), 616-626.
- _____. (1986). "Suspended sediment concentrations under waves," *Coastal Eng.* 10, 23-31.
- O'Conner, B. A., and Nicholson, J. (1988). "A three dimensional model of suspended particulate sediment transport," *Coastal Eng.* 12, 157-174.
- Osborne, P. D., and Greenwood, B. (1992). "Frequency dependent cross-shore suspended sediment transport; 1, A non-barred shoreface," *Marine Geology* 106 (1-2), 1-24.
- _____. (1992). "Frequency dependent cross-shore suspended sediment transport; 2, A barred shoreface," *Marine Geology* 106 (1-2), 25-51.
- Ostendorf, D. W. (1982). "Longshore dispersion over a flat beach," *J. Geophys. Res.* 87 (C6), 4241-4248.
- Ribberink, J. S., and Al-Salem, A. (1990). "Bedforms, sediment concentrations and sediment transport in simulated wave conditions." *22nd Coastal Engineering Conference*. B. L. Edge, ed., American Society of Civil Engineers, 2318-2331.
- Sawaragi, T., and Deguchi, I. (1987). "On-offshore sediment transport rate in the surf zone." *17th Coastal Engineering Conference*. American Society of Civil Engineers, 1481-1495.

- Sheng, Y. P., and Villaret, C. (1989). "Modeling the effect of suspended sediment stratification on bottom exchange processes," *Journal Of Geophysical Research-Oceans* 94 (C10), 14429-14444.
- Shibayama, T., and Horikawa, K. (1980). "Bedload measurement and prediction of two-dimensional beach transformation due to waves," *Coastal Engineering in Japan* 23, 179-190.
- Shore protection manual.* (1984). 4th ed., 2 Vol, U.S. Army Engineer Waterways Experiment Station, U.S. Government Printing Office, Washington, DC.
- Skafel, M. G., and Krishnappan, B. G. (1984). "Suspended sediment distribution in wave field," *Journal of Waterway, Port, Coastal and Ocean Engineering* 110 (2), 215-230.
- Sleath, J. F. A. (1984). *Sea bed mechanics.* John Wiley and Sons, New York.
- Soulsby, R. L., and Wainwright, B. L. S. A. (1987). "A criterion for the effect of suspended sediment on near-bottom velocity profiles," *Journal of Hydraulic Research* 25 (3), 341-356.
- Sternberg, R. W., Kineke, G. C., and Johnson, R. (1991). "An instrument system for profiling suspended sediment, fluid, and flow conditions in shallow marine environments," *Cont. Shelf Res.* 11 (2), 109-122.
- Stive, M. J. F., and de Vriend, H. J. (1987). "Quasi-3D nearshore current modelling: Wave-induced secondary current." *Conference on Coastal Hydrodynamics.* American Society of Civil Engineers, 356-370.
- Swart, D. H. (1976). "Predictive equations regarding coastal transports." *15th Coastal Engineering Conference.* American Society of Civil Engineers, 1113-1132.
- van Rijn, L. C. (1984). "Sediment transport : Suspended load transport," *J. Hydr. Eng.* 110 (11), 1613-1641.
- van Rijn, L. C., and Kroon, A. (1992). "Sediment transport by currents and waves." *23rd International Conference on Coastal Engineering.* B. L. Edge, ed., American Society of Civil Engineers, 2613-2628.
- Vongvisessomjai, S. (1986). "Profile of suspended sediment due to wave action," *Journal of Waterway, Port, Coastal and Ocean Engineering* 112 (1), 35-53.
- Wang, Z. B. (1992). "Theoretical analysis on depth-integrated modelling of suspended sediment transport," *Journal Of Hydraulic Research* 30 (3), 403-421.

- Watanabe, A. (1982). "Total rate and distribution of longshore sand transport," *Coastal Engineering in Japan* 25, 147-161.
- _____. (1992). "Total rate and distribution of longshore sand transport." *23rd International Conference on Coastal Engineering*. B. L. Edge, ed., American Society of Civil Engineers, 2528-2541.
- Wu, C.-S., Thornton, E. B., and Guza, R. T. (1985). "Waves and longshore currents: Comparison of a numerical model with field data," *Journal of Geophysical Research* 90 (C3), 4951-4958.
- Zyserman, J. A. (1992). "A critical review of available data for calibration and/or verification of sediment transport models." *23rd International Conference on Coastal Engineering*. B. L. Edge, ed., American Society of Civil Engineers, 2567-2580.

Appendix A

Notation

The notation adopted herein attempts to use commonly accepted symbols whenever possible. Coordinate systems are all right-handed, but in some cases the x -coordinate is parallel to the sloping planar bed while in others the x - y coordinate plane is horizontal. Except where noted, angle brackets are used to denote a temporal or ensemble average; overbars indicate a spatial average; tildes indicate an oscillatory component; and primes indicate a fluctuating component. The subscripts b and 0 refer to quantities evaluated at the bed, although the location of the nominal bed elevation differs in various theories. The symbol $[\emptyset]$ denotes a dimensionless quantity.

c	Wave phase velocity	$[LT^{-1}]$
c_f	Friction factor or bed drag coefficient	$[\emptyset]$
c_g	Group velocity	$[LT^{-1}]$
c_r	Coefficient in Equation 21	$[\emptyset]$
dh/dx	Bed slope	$[\emptyset]$
e_b	Bed-load efficiency factor	$[\emptyset]$
e_s	Suspended load efficiency factor	$[\emptyset]$
f	Wave frequency	$[T^{-1}]$
f_p	Peak wave frequency	$[T^{-1}]$
f_w	Wave friction factor	$[\emptyset]$
g	Gravitational acceleration	$[L T^{-2}]$
h	Water depth	$[L]$
i	Immersed weight sediment transport rate per unit width	$[ML^{-1} T^{-1}]$

i_{θ}	Immersed weight sediment transport rate in θ direction	$[ML^{-1} T^{-1}]$
\hat{i}	Unit vector in x -direction (offshore)	$[\emptyset]$
k	Wave number ($= 2 \pi L^{-1}$)	$[L^{-1}]$
k_t	Turbulent kinetic energy per unit mass	$[L^2 T^{-2}]$
m	Exponent defined in Equation 36	$[\emptyset]$
n	Exponent defined in Equation 33	$[\emptyset]$
s	Ratio of grain and fluid densities	$[\emptyset]$
t	Time	$[T]$
u	Water velocity in x -direction	$[LT^{-1}]$
u_*	Friction or shear velocity	$[LT^{-1}]$
u_m	Maximum orbital wave velocity	$[LT^{-1}]$
u_{θ}	Current velocity in θ -direction	$[LT^{-1}]$
\vec{u}	Instantaneous fluid velocity	$[LT^{-1}]$
v	Water velocity in y -direction	$[LT^{-1}]$
w	Water velocity in z -direction	$[LT^{-1}]$
x	Horizontal coordinate (+offshore)	$[L]$
y	Horizontal coordinate	$[L]$
z	Vertical coordinate (+up)	$[L]$
A	Profile shape parameter	$[L^{1/3}]$
A_g	Constant defined in Equation 34	$[\emptyset]$
B	Coefficient in Equation 13	$[\emptyset]$
C_g	Constant defined in Equation 35	$[\emptyset]$
D	Mean sediment grain diameter	$[L]$
D_*	Dimensionless sediment grain diameter	$[\emptyset]$
E	Energy dissipation rate per unit volume	$[M L^{-1} T^{-3}]$

E_{eq}	Equilibrium energy dissipation rate per unit volume	$[M L^{-1} T^{-3}]$
F_*	Dimensionless mobility parameter	$[\emptyset]$
G_*	Dimensionless transport parameter	$[\emptyset]$
H	Wave height	$[L]$
H_0	Deepwater wave height	$[L]$
H_s	Significant wave height	$[L]$
H_{rms}	Root-mean-square wave height	$[L]$
L	Wave length	$[L]$
K	Coefficient in Equation 24	$[L^3 M^{-1} T^2]$
K_B	Coefficient in Equation 3	$[L^{-1} T^2]$
K_1	Coefficient in Equation 6	$[L^3 T^{-2}]$
K_2	Coefficient in Equation 6	$[L^{-1} T]$
M	Coefficient in Equation 24	$[\emptyset]$
N	Volume concentration	$[\emptyset]$
N_{bed}	Volume concentration of randomly packed particles	$[\emptyset]$
S	Energy slope in unidirectional flow	$[\emptyset]$
R	Rouse number	$[\emptyset]$
T	Wave period	$[T]$
U_1	Perturbation velocity	$[LT^{-1}]$
W	Sediment fall velocity	$[LT^{-1}]$
α	Wave angle (deviation from normal)	[radians]
β	Bed slope	$[\emptyset]$
β_d	Coefficient in Equation 11	$[\emptyset]$
ϵ_d	Energy dissipation rate	$[M T^{-3}]$
$\epsilon\beta$	Coefficient in Equation 24	$[M T^{-3}]$

γ	Ratio of wave height to water depth	[\emptyset]
γ_b	Ratio of wave height to water depth at breaking	[\emptyset]
κ	von Karman's constant (= 0.4)	[\emptyset]
θ	Shield's parameter	[\emptyset]
ρ	Fluid density	[M L ⁻³]
ρ_s	Sediment density	[M L ⁻³]
σ	Radial wave frequency	[T ⁻¹]
τ_b	Bed shear stress	[M L ⁻¹ T ⁻²]
ν	Kinematic viscosity	[L ² T ⁻¹]
ν_s	Sediment diffusivity	[L ² T ⁻¹]
ω	Wave or stream power	[M T ⁻³]

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE October 1995	3. REPORT TYPE AND DATES COVERED Final report	
4. TITLE AND SUBTITLE Compilation of Suspended-Load Point-Transport Theories			5. FUNDING NUMBERS	
6. AUTHOR(S) Thomas G. Drake, Thomas E. White				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Evans-Hamilton, Inc. 7214 S. Kirkwood, Houston, TX 77072 U.S. Army Engineer Waterways Experiment Station 3909 Halls Ferry Road, Vicksburg, MS 39180-6199			8. PERFORMING ORGANIZATION REPORT NUMBER Technical Report CERC-95-18	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Corps of Engineers Washington, DC 20314-1000			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Available from National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The purpose of this report is to survey the available literature for theories that predict the transport of cohesionless sediments by suspension in the surf zone in combined wave-current nearshore flows under conditions such that quasi-unidirectional currents do not dominate the combined flow. The selected formulae will form a basis for testing theoretical predictions with field measurements of suspended-sediment transport and requisite fluid and sediment quantities at a point within the surf zone or immediately adjacent to it. For each of the unique theories, a common set of variables is used to formulate an explicit mathematical expression for the suspended sediment transport rate. Redundant theories are those which differ only by numerical coefficients from any of the unique theories, having otherwise the same functional form. Accompanying each unique formula is an outline of its derivation, and a list of the assumptions underlying the derivation.				
14. SUBJECT TERMS Literature search Suspended-sediment transport Transport theories			15. NUMBER OF PAGES 40	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	